

DEVBULK SARE

Built / Ship Yard:	Feb 2012 / Naikai , Japan		
Flag:	Marshall Islands		
Class:	RINA		
P&I Club:	Uk Club		
Type:	Bulk Carrier		
Dwt:	40,445 mts on 10,47 m Summer Draft		
Tpc:	51,3 mt on Summer Draft		
L.o.a.:	184,75 m		
Beam:	30,60 m		
Light Ship:	8479 mt		
Moulded Depth:	14,50 m		
Tonnage Gt / Nt	23,950/ 11,814		
	<u>Summer</u>	<u>Winter</u>	<u>Tropical</u>
Deadweight	40,445 mts	39,318 mts	41,577 mts
Draft	10,47 m	10,25 m	10,68 m
Freeboard	4,074 m	4,292 m	3,856 m
Hatch Cover Size:	No		
	1	15,52 m x 17,60 m	
	2	20,80 m x 20,80 m	
	3	20,80 m x 20,80 m	
	4	23,26 m x 20,80 m	
	5	20,80 m x 20,80 m	
Hold Capacity:	No	Grain / Bale (Cub.m)	
	1	7,592 / 7,410	
	2	10,304 / 10,082	
	3	10,304 / 10,082	
	4	10,360 / 10,175	
	5	8,673 / 8,564	
	Total	47,235 / 46,315	
Type of Hatch Cover:	Hydraulic folding Type		
Gear:	4 Cranes x 30,0 mts Swl		
Grab:	N/A		
Ventilation/A60/CO2/ITF	Nat / Yes / No / Yes		
Tanktop Strength:	H1:18.5, H2:12.2, H3:20.1, H4:12.2, H5:19.5 mts/sqm		
Hatch Cover Strength:	H1:2.52, H2:2.96, H3:3.07, H4:3.07, H5:3.07 mts/sqm		
Main Engine:	HITACHI MAN B&W 6S46MC-C / MARK 7		
Generators:	6EY18ALx480KW x 900RPM x 3 Sets		
Bunker Capacity %85:	Visifo : 1.411 m3 & Lsmgo : 631 m3		
Speed/Consumption:			
Laden Condition:	Abt 12,00 Knots on abt 17,50 mt Visifo + 0,1 mt Lsmgo		
Ballast Condition:	Abt 12,50 Knots on abt 17,50 mt Visifo + 0,1 mt Lsmgo		
Port Consumption:	Abt 2,5 mt Visifo + 0,1 mt Lsmgo		
Winches Working:	Abt 5,6 mt Visifo + 0,1 mt Lsmgo		
	Note: Local port regulations require the burning of Lsmgo in port, e.g. EU ports		

ALL ABT.TAKEN PLAN BUT WITHOUT GUARANTEE